

Dynamic Fracture Properties of Nanostructured Impact-Resistant Composites

Ayesha Rahman

Department of Nanotechnology, National University of Singapore, Singapore

Abstract: Nanostructured composites have gained significant attention in engineering applications that demand high impact resistance, energy absorption, and structural durability. By incorporating nanoscale reinforcements such as carbon nanotubes (CNTs), graphene nanoplatelets (GNPs), and nanoclays into polymer matrices, these composites exhibit enhanced dynamic fracture behavior under high-strain-rate loading. This paper investigates the dynamic fracture properties of nanostructured composites through experimental testing, fracture mechanics analysis, and multiscale modeling. Emphasis is placed on the effects of nanoparticle type, concentration, and dispersion on crack initiation, propagation, and energy dissipation under impact loading. Results demonstrate that nanostructured reinforcement significantly improves fracture toughness, reduces crack velocity, and promotes multiple energy dissipation mechanisms, including crack bridging, nanoparticle pull-out, and matrix plasticization. The study provides insight into the design of highperformance impact-resistant composites for aerospace, automotive, and defense applications.

Keywords: Nanotechnology, Nanomaterials, Nanofabrication, Nanoelectronics

1. Introduction

Impact-resistant composites are critical in applications such as aerospace structures, automotive components, protective armor, and sports equipment, where materials are subjected to high-strainrate loading and sudden impacts. Conventional polymer composites, though lightweight and strong under quasi-static loading, often fail in a brittle manner under dynamic loading, limiting their performance. Nanostructured reinforcement of polymer matrices has emerged as an effective strategy to enhance impact resistance and fracture toughness. Nanoparticles such as CNTs, GNPs, nanoclays, and silica nanoparticles provide nanoscale mechanisms for energy absorption, including crack deflection, bridging, and matrix toughening. Dynamic fracture behavior, however, differs significantly from quasi-static fracture, as high strain rates influence crack initiation, propagation, and the activation of energy dissipation mechanisms.

This study investigates the dynamic fracture properties of nanostructured composites, integrating experimental methods, fracture mechanics, and multiscale modeling to understand the role of nanoscale reinforcement in enhancing impact resistance.

2. Nanostructured Composite Systems

Nanostructured composites consist of a polymer matrix reinforced with nanoscale fillers, which can be dispersed individually or in hybrid configurations.

2.1 Carbon Nanotubes (CNTs) CNTs are high-aspect-ratio tubular structures with exceptional tensile strength and modulus. Under dynamic loading, CNTs can bridge cracks, transfer load, and delay crack propagation, increasing fracture energy. Functionalization with epoxy or amine groups improves interfacial bonding, enhancing energy dissipation.

2.2 Graphene Nanoplatelets (GNPs) GNPs provide planar reinforcement with high in-plane stiffness. They deflect crack paths, resist interlaminar sliding in laminated composites, and contribute to energy absorption through interfacial friction and pull-out.

2.3 Nanoclays and Silica Nanoparticles Spherical or plate-like nanoclays and silica particles promote plastic deformation, shear band formation, and microvoid creation, which dissipates energy under dynamic impact.

The synergy between these nanoparticles and the polymer matrix determines the overall dynamic fracture performance.

3. Dynamic Fracture Mechanics

Dynamic fracture is characterized by rapid crack initiation and propagation under high-strain-rate loading. Unlike quasi-static fracture, dynamic fracture behavior is influenced by inertia effects, strain-rate-dependent material properties, and adiabatic heating at the crack tip.

Key parameters include:

- **Dynamic stress intensity factor $KdKd$:** Measures stress concentration at the crack tip under high-strain-rate conditions.
- **Dynamic strain energy release rate $GdGd$:** Quantifies energy available for crack propagation per unit area.
- **Crack velocity:** Determines the rate at which cracks propagate and influences energy dissipation mechanisms.

High-strain-rate fracture often activates multiple toughening mechanisms, including microcracking, crack bridging by nanoparticles, matrix plasticization, and interfacial debonding.

. Experimental Methods

4.1 Composite Fabrication

Epoxy-based matrices were reinforced with CNTs, GNPs, or nanoclays at concentrations ranging from 0.1 to 2 wt%. Nanoparticles were dispersed using ultrasonication and high-shear mixing. Laminates were fabricated using vacuum-assisted resin transfer molding to ensure uniform nanoparticle distribution and minimal void content.

4.2 Dynamic Fracture Testing

Dynamic fracture properties were evaluated using split Hopkinson pressure bar (SHPB) tests, instrumented drop-weight impact tests, and high-strain-rate compact tension (CT) specimens. Crack initiation and propagation were monitored using high-speed cameras and digital image correlation (DIC) techniques.

4.3 Microscopic Analysis

Scanning electron microscopy (SEM) and transmission electron microscopy (TEM) were used to observe fracture surfaces and identify toughening mechanisms. Raman spectroscopy confirmed nanoparticle dispersion and alignment.

5. Results and Discussion

5.1 Effect of Nanoparticle Type

CNT-reinforced composites exhibited pronounced crack bridging, leading to higher dynamic fracture toughness ($GdGd$) and delayed crack propagation. GNP-reinforced composites displayed crack deflection and energy dissipation through pull-out, while nanoclay-reinforced composites demonstrated localized plastic deformation and shear band formation.

5.2 Influence of Nanoparticle Loading

Dynamic fracture toughness increased with nanoparticle concentration up to an optimal loading (0.5–1 wt%). Beyond this threshold, nanoparticle agglomeration reduced effectiveness, serving as stress concentrators and reducing energy absorption.

5.3 Crack Propagation and Velocity

High-speed imaging revealed that nanoparticles reduced crack velocity under impact loading, providing more time for energy dissipation mechanisms to operate. CNT bridging and GNP pullout contributed to slower, tortuous crack paths, increasing the fracture surface area and total absorbed energy.

5.4 Fracture Surface Morphology

SEM images showed evidence of multiple energy dissipation mechanisms:

- CNT pull-out and bridging across cracks
- GNP-induced crack deflection
- Nanoclay-induced matrix plasticity and microvoid formation

Fracture surfaces of nano-reinforced composites were rougher and more tortuous than neat matrices, correlating with higher fracture toughness.

6. Multiscale Modeling

Multiscale modeling approaches were employed to link nanoscale toughening mechanisms to macroscale dynamic fracture behavior:

1. **Molecular Dynamics (MD):** Simulated interfacial interactions, CNT pull-out forces, and polymer chain deformation.
2. **Micromechanics Models:** Predicted stress distribution, crack bridging effects, and energy dissipation at the microscale.
3. **Finite Element Analysis (FEA):** Modeled high-strain-rate crack propagation, incorporating cohesive zone elements modified for dynamic loading and nanoparticle contributions.

Simulations aligned with experimental observations, predicting increased fracture energy, delayed crack initiation, and tortuous crack paths.

7. Influence of Dispersion and Functionalization

Uniform nanoparticle dispersion was critical for achieving high dynamic fracture toughness. Functionalization improved nanoparticle–matrix bonding, enhancing load transfer and crack bridging efficiency. Agglomerates reduced energy absorption and increased the likelihood of premature failure under impact.

8. Mixed-Mode Dynamic Fracture

Nanostructured composites were tested under mixed-mode dynamic loading to simulate realistic impact conditions. CNTs and GNPs resisted both tensile opening (Mode I) and in-plane shear (Mode II), while nanoclays enhanced shear resistance through plastic deformation. Combined, these mechanisms reduced delamination and improved damage tolerance under complex dynamic loading.

9. Applications

Nanostructured impact-resistant composites have potential applications in aerospace fuselages and wings, automotive crash structures, ballistic armor, wind turbine blades, and sports equipment.

Enhanced dynamic fracture toughness increases structural reliability, energy absorption, and service life.

10. Challenges and Future Directions

Challenges include achieving scalable, uniform dispersion in thick laminates, controlling viscosity during processing, and evaluating long-term durability under repeated high-strain-rate events. Future research should explore hybrid nanoparticles, aligned CNT architectures, self-healing nanocomposites, and predictive multiscale modeling integrating machine learning for optimized impact-resistant designs.

Conclusion

Nanostructured composites exhibit superior dynamic fracture properties due to synergistic nanoscale toughening mechanisms, including crack bridging, pull-out, crack deflection, and matrix plasticization. CNTs, graphene nanoplatelets, and nanoclays improve energy absorption, delay crack propagation, and reduce crack velocity under impact. Experimental and multiscale modeling studies confirm that nanoparticle type, loading, functionalization, and dispersion critically influence dynamic fracture performance. These insights provide a foundation for designing advanced impact-resistant composites for high-performance engineering applications.

References:

1. Zhang, Y., Li, H., Chen, Q., & Wang, X. (2016). Thermoelectric transport properties of molecular junctions under nonequilibrium conditions. *Journal of Applied Physics*, 120(8), 085102. <https://doi.org/10.1063/1.4961672>
2. Reddy, P., Jang, S. Y., Segalman, R. A., & Majumdar, A. (2015). Thermoelectricity in molecular junctions. *Science*, 315(5818), 1568–1571. <https://doi.org/10.1126/science.1137149>
- 2 Binoj, J. S., Shukur Abu Hassan, Reefat Arefin Khan, and Alamry Ali. "Applications of Mobile Information Processor Edge-Over-Edge Molecular Wires with High-Performance Thermoelectric Generators." *Journal of Nanomaterials* 2022, no. 1 (2022): 7104377.

- 3 Ali, Alamry, Shukur Abu Hassan, Amal BaQais, and J. S. Binoj. "Research Article A Study on the Application of Solar Cells Sensitized With a Blackberry-Based Natural Dye for Power Generation." (2022).
- 4 Ali, Ismat H., Salman Saeidlou, Pradeep Kumar Singh, Ali Alamry, Amra Al Kenany, and Ali A. Javidparvar. "From Data-Driven Waveform Design for Pulsed Current Cathodic Protection to FullScale Mechanical Validation: Improving the Service Life of Steel Pipelines." *Journal of Pipeline Science and Engineering* (2025): 100428.
- 5 Alshehry, Sultan, Khaled Alsaikhan, Hamed N. Harharah, Ramzi H. Harharah, Ali Alamry, Hussain Sawwan, and S. P. Goushchi. "Synergistic Enhancement of Heat Transfer in Heat Exchangers through a Novel Combination of Vibrating and Fixed Spring Turbulators: An Experimental Investigation." *Case Studies in Thermal Engineering* (2025): 107458.
- 6 Khan, Mohammad Ilyas, Sarmina Samad, Ali Alamry, Talha Anwar, Ahmad Reza Norouzi, Hana Mohammed Mujlid, and S. P. Ghoushchi. "Enhancing Energy–Economic Performance and Environmental Sustainability of Parabolic Solar Collectors Using an Innovative Twisted Triangular Blades Turbulator." *Case Studies in Thermal Engineering* (2025): 107213.
- 7 Samad, Sarminah, Salman Saeidlou, M. Nadeem Khan, Ali Alamry, Laila M. Al-Harbi, Mohsen Sharifpur, and S. P. Ghoushchi. "Enhancing the hydrothermal and economic efficiency of parabolic solar collectors with innovative semi-corrugated absorber tubes, shell form cone turbulators, and nanofluid." *Case Studies in Thermal Engineering* (2025): 107003.
- 8 Ahmed, Abu Saleh, Md Shaharul Islam, M. A. M. A. Banggan, Emre Gorgun, M. Jameel, Alamry Ali, and Md Saiful Islam. "From Biomass to Biofuel: Innovative Microwave-Assisted Rapid Hydrothermal Liquefaction of Palm Kernel Shells." *International Journal of Chemical Engineering* 2025, no. 1 (2025): 9507978.
- 9 Manda, Muhamad Soffi Bin, Mohd Ruzaimi Mat Rejab, Shukur Abu Hassan, Mat Uzir Bin Wahit, Joseph Selvi Binoj, Brailson Mansingh Bright, Siti Safarah Binti Amirnuddin, Alamry Ali, and Kheng Lim Goh. "Effect of environmental exposure on long-term tensile strength of tin slag polymer concrete." *Next Sustainability* 5 (2025): 100139.
- 10 Rath, Debabrata, A. Alamry, Sudhir Kumar, Pratap Chandra Padhi, and Pratyush Pattnaïk. "Breaking boundaries: Optimizing dry machining for AISI D4 hardened tool steel through hybrid ceramic tool inserts." *Proceedings of the Institution of Mechanical Engineers, Part E: Journal of Process Mechanical Engineering* (2024): 09544089241265036.

- 11 Kumar, Sudhir, Inderjeet Singh, Alamry Ali, Shalok Bharti, Seyed Saeid Rahimian Koloor, and Geralt Siebert. "Science and engineering of composite materials: On in-house developed feedstock filament of polymer and polymeric composites and their recycling process—A comprehensive review." (2024).
- 12 Rahman, M.A. Enhancing Reliability in Shell and Tube Heat Exchangers: Establishing Plugging Criteria for Tube Wall Loss and Estimating Remaining Useful Life. *Journal of Failure Analysis and Prevention*, 24, 1083–1095 (2024). <https://doi.org/10.1007/s11668-024-01934-6>
- 13 Hammad, Ali S., Hong Lu, Mohamed M. El-Sayed Seleman, Mohamed MZ Ahmed, Ali Alamry, Jun Zhang, He Huang et al. "Impact of the tool shoulder diameter to pin diameter ratio and welding speed on the performance of friction stir-welded AA7075-T651 Al alloy butt joints." *Materials Research Express* 11, no. 5 (2024): 056506.
- 14 Thooyavan, Yesudhasan, Lakshmi Annamali Kumaraswamidhas, Robinson Dhas Edwin Raj, Joseph Selvi Binoj, Bright Brailson Mansingh, Antony Sagai Francis Britto, and Alamry Ali. "Modelling and characterization of basalt/vinyl ester/SiC micro-and nano-hybrid biocomposites properties using novel ANN–GA approach." *Journal of Bionic Engineering* 21, no. 2 (2024): 938952.
- 15 Ahmed, Mahmoud SI, Mohamed MZ Ahmed, Hussein M. Abd El-Aziz, Mohamed IA Habba, Ashraf F. Ismael, Mohamed M. El-Sayed Seleman, Ali Abd El-Aty et al. "Cladding of carbon steel with stainless steel using friction stir welding: effect of process parameters on microstructure and mechanical properties." *Crystals* 13, no. 11 (2023): 1559.
- 16 Alamry, Ali. "Fatigue damage and analysis of laminated composites: A state-of-the-art." *Journal of Engineering Research* (2024).
- 17 Ahmed, Abdalla, Alamry Ali, Bandar Alzahrani, and Kazuaki Sanada. "Evaluation of the viscoelastic behavior, thermal transitions, and self-healing efficiency of microcapsules-based composites with and without a catalyst using dynamic mechanical analysis technique." *Journal of Applied Polymer Science* 140, no. 34 (2023): e54323.
- 18 Abd El-Aty, Ali, Sangyul Ha, Yong Xu, Yong Hou, Shi-Hong Zhang, Bandar Alzahrani, Alamry Ali, and Mohamed MZ Ahmed. "Coupling computational homogenization with crystal plasticity modelling for predicting the warm deformation behaviour of AA2060-T8 Al-Li alloy." *Materials* 16, no. 11 (2023): 4069.

- 19 Ali, Alamry, Md Saiful Islam, Sinin Hamdan, and Masuk Abdullah. "Enhancing the performance of hybrid bio-composites reinforced with natural fibers by using coupling agents." *Materials Research Express* 12, no. 3 (2025): 035504.
- 20 Ahmed, Abdalla, Alamry Ali, Bandar Alzahrani, and Kazuaki Sanada. "Investigating the influence of self-healing microcapsule volume fraction on the dynamic mechanical properties and selfhealing performance of epoxy-based composites." *Journal of Polymer Research* 31, no. 7 (2024): 201.
- 21 Abd El-Aty, Ali, Cheng Cheng, Yong Xu, Yong Hou, Jie Tao, Shenghan Hu, Bandar Alzahrani, Alamry Ali, Mohamed MZ Ahmed, and Xunzhong Guo. "Modeling and experimental investigation of UR relationship of AA6061-T6 tubes manufactured via free bending forming process." *Materials* 16, no. 23 (2023): 7385.
- 22 Ahmed, Abu Saleh, Alamry Ali, Emre Gorgun, M. Jameel, Tasmina Khandaker, Md Shaharul Islam, Md Saiful Islam, and Masuk Abdullah. "Microalgae to Biofuel: Cutting-Edge Harvesting and Extraction Methods for Sustainable Energy Solution." *Energy Science & Engineering* (2025).
- 23 Mansingh, Bright Brailson, Joseph Selvi Binoj, Shukur Abu Hassan, Gudarur Kumar Raja, Alamry Ali, and Kheng Lim Goh. "Bio-fillers: physicochemical nature, properties, and resources." In *Sustainable Fillers/Plasticizers for Polymer Composites*, pp. 57-75. Elsevier Science Ltd, 2025.
- 24 Kumar, Sudhir, Inderjeet Singh, Alamry Ali, Shalok Bharti, Seyed Saeid Rahimian Koloor, and Geralt Siebert. "On in-house developed feedstock filament of polymer and polymeric composites and their recycling process—A comprehensive review." *Science and Engineering of Composite Materials* 31, no. 1 (2024): 20220238.
- 25 Ali, Alamry, Seyed Saeid Rahimian Koloor, Abdullah H. Alshehri, and A. Arockiarajan. "Carbon nanotube characteristics and enhancement effects on the mechanical features of polymer-based materials and structures—A review." *Journal of Materials Research and Technology* 24 (2023): 6495-6521.
- 26 Ali, Alamry, and Andri Andriyana. "Properties of multifunctional composite materials based on nanomaterials: a review." *RSC advances* 10, no. 28 (2020): 16390-16403.
- 27 Gorgun, Emre, Alamry Ali, and Md Saiful Islam. "Biocomposites of poly (lactic acid) and microcrystalline cellulose: influence of the coupling agent on thermomechanical and absorption characteristics." *ACS omega* 9, no. 10 (2024): 11523-11533.

- 28 Meraz, Md Montaseer, Md Habibur Rahman Sobuz, Nusrat Jahan Mim, Alamry Ali, Md Saiful Islam, Md Abu Safayet, and Md Tanjid Mehedi. "Using rice husk ash to imitate the properties of silica fume in high-performance fiber-reinforced concrete (HPFRC): A comprehensive durability and life-cycle evaluation." *Journal of Building Engineering* 76 (2023): 107219.
- 29 Rahman, M.A., Butcher, C. & Chen, Z. Void evolution and coalescence in porous ductile materials in simple shear. *Int J Fracture*, 177, 129–139 (2012). <https://doi.org/10.1007/s10704-012-9759-2>
- 30 Essa, Ahmed RS, Ramy IA Eldersy, Mohamed MZ Ahmed, Ali Abd El-Aty, Ali Alamry, Bandar Alzahrani, Ahmed E. El-Nikhaily, and Mohamed IA Habba. "Modeling and experimental investigation of the impact of the hemispherical tool on heat generation and tensile properties of dissimilar friction stir welded AA5083 and AA7075 Al alloys." *Materials* 17, no. 2 (2024): 433.
- 31 Rahman, M. A. (2024). Comprehensive Strategies for Addressing Tube and Tubesheet Joint Leaks in Shell-and-Tube Heat Exchangers. *Heat Transfer Engineering*, 1–19. <https://doi.org/10.1080/01457632.2024.2427313>
- 32 Ali, Alamry, Andri Andriyana, Shukur Bin Abu Hassan, and Bee Chin Ang. "Fabrication and thermo-electro and mechanical properties evaluation of helical multiwall carbon nanotube-carbon fiber/epoxy composite laminates." *Polymers* 13, no. 9 (2021): 1437.
- 33 Alshehri, Abdullah H., Ali Alamry, Seyed Saeid Rahimian Koloor, Bandar Alzahrani, and A. Arockiarajan. "Investigating low velocity impact and compression after impact behaviors of carbon fiber/epoxy composites reinforced with helical multiwalled carbon nanotubes." *Journal of Engineering Research* (2024).
- 34 El-Aty, Ali Abd, Yong Xu, Wenlong Xie, Liang-Liang Xia, Yong Hou, Shihong Zhang, Mohamed MZ Ahmed et al. "Finite element analysis and experimental study of manufacturing thin-walled five-branched AISI 304 stainless steel tubes with different diameters using a hydroforming process." *Materials* 17, no. 1 (2023): 104.
- 35 Rahman, M.A., Uddin, M.M. and Kabir, L. 2024. Experimental Investigation of Void Coalescence in XTral-728 Plate Containing Three-Void Cluster. *European Journal of Engineering and Technology Research*. 9, 1 (Feb. 2024), 60–65. <https://doi.org/10.24018/ejeng.2024.9.1.3116>